## Drop-in RTR Cold Well

Models: ☐ RTR-4Di

PRODUCT: QUANTITY: ITEM:

### **Designed Smart**

### **Compact Design with High Output**

The Drop-In Cold Well provides an economic solution to the cost of in-counter refrigeration

- · User R-134a refrigerant
- Holds 4 pans 1/6<sup>th</sup> size by 6" deep.
- Each pan has its own hinged, removable cover.
- · All pans are completely removable for easy cleaning.
- Cold well refrigeration system utilizes a 1/6 HP compressor.

### **APW Wyott Design Features**

- User R-134a refrigerant
- Holds 4 pans 1/6<sup>th</sup> size by 6" deep.
- Each pan has its own hinged, removable cover.
- All pans are completely removable for easy cleaning.
- Cold well refrigeration system utilizes a 1/6 HP compressor.

### **Option and Accessories**

- COMP-5 5-year compressor warranty
- 4" deep polycarbonate food wells with hinged acrylic covers.



# Reliability backed by APW Wyott's Warranty

APW Wyott Drop-In Cold Wells are backed by a 1-year parts and labor warranty, including on-site service calls within 50 miles of authorized service, technicians.

## Certified by the following agencies:







See reverse side for product specifications.








## Drop-in RTR Cold Well

Models: ☐ RTR-4Di

PRODUCT: QUANTITY: ITEM:







Cut out Size +/- I/4

### PRODUCT SPECIFICATIONS

#### **Construction:**

Interior is stainless steel exterior is aluminized steel. Utilizes a 1/6<sup>th</sup> HP compressor. RTR-4Di comes with 4 hinged polycarbonate pans. Refrigeration is a cold wall system and utilizes a R-134a (CFC free) refrigerant.

#### **Electrical Specifications:**

RTR-4Di: 120V, 360W, 60 Hz, 1 Ph, 3 Amps

#### Capacity:

RTR-4Di holds (4) 1/6th size 6" deep pans.

#### **Dimensions:**

RTR-4Di:  $7^{-13}/_{32}$ "L x  $16^{-13}/_{32}$ "W x  $1^{-3}/_4$ "H

Recommended Cutout  $16^{-11}/_{16}$ " x  $15^{-11}/_{16}$ "

### Shipping:

Weight: 67 Lbs Freight Class: 70 FOB: Allen, TX 75013

\*APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.

