



The Signature of Quality

FEDERAL INDUSTRIES

A Standex Company

215 Federal Avenue Belleville
Wisconsin 53508-9201

Phone: 800-356-4206

Fax: 608-424-3234

Email: Geninfo@Federalind.com

Website: Federalind.com

Project Name: _____

Item #: _____

Model #: _____ Qty: _____

Approval: _____

AIA #

SIS #

Italian Glass Refrigerated Display Case

Ideal for both Bakery & Deli Merchandising

Designed for customers looking for rich, up-scale Italian styling for maximum visual appeal that will drive product sales. Cases are available in lengths of 36", 48", and 60"



Model ITR6034-B18
Shown with optional laminate

OPTIONAL ACCESSORIES

- ☐ Special Base Laminates
- ☐ Condensate Pump
- ☐ Cord & Plug (SC models only)
- ☐ Stainless Steel Shelving
- ☐ Reflective Rear Doors
- ☐ Reflective Ends
- ☐ Front Air Intake & Discharge
- ☐ 4"/102mm Casters
- ☐ Recessed Casters
- ☐ 6"/152mm Legs With or Without Skirt
- ☐ Rear Package Shelf
- ☐ Remote Condensing Unit
- ☐ Joining Kit for Continuous Line-Ups

MODEL	LENGTH (Includes End Panels)
☐ ITR3626-B18	36 x 30.75 x 44 (in) 914 x 781 x 1118 (mm)
☐ ITR4826-B18	48 x 30.75 x 44 (in) 1219 x 781 x 1118 (mm)
☐ ITR6026-B18	60 x 30.75 x 44 (in) 1524 x 781 x 1118 (mm)
☐ ITR3634-B18	36 x 30.75 x 52 (in) 914 x 781 x 1321 (mm)
☐ ITR4834-B18	48 x 30.75 x 52 (in) 1219 x 781 x 1321 (mm)
☐ ITR6034-B18	60 x 30.75 x 52 (in) 1524 x 781 x 1321 (mm)

STANDARD FEATURES

Model Features

- Powder coated steel base construction with a choice of six standard laminates
- Stainless steel interior
- All tempered thermo-pane glass construction
- Tilt out front glass for easy cleaning
- Removable sliding glass rear doors
- Leg levelers
- Rear air intake and discharge.

Refrigeration

- Electronic temperature control with on demand defrost
- PTC Condensate evaporator provided for a totally self-contained system
- Easily accessible light switch, power switch, and electronic temperature control
- Average product temperature of 38°F (3.3°C) to 40°F (4.4°C)
- R134A Refrigerant

Shelving

- Adjustable tempered glass shelves. Shelves are adjustable up and down and can be tilted in two positions (0°/5° angle). 34" (864mm) models have three tiers of shelves; 26" (660mm) models have two tiers of shelves

Lighting

- 3500K LED top light and shelf lights
- DLC Certified, IP66 rated

Agency Approvals

- UL, C-UL, and UL Sanitation Listed to NSF-7, Type II conditions
- DOE 2017 Compliant



WARRANTY*
One year Parts and Labor
2nd thru 5th year part only
service compressor
(U.S.A. and Canada)

Note: Information is subject to change at any time. Visit www.federalind.com For the most current specs.

